



Mingda Bearing Products co., LTD



6006 Bearing 2D drawings and 3D CAD models

6006 C3- O&Kai Z1V1 Z2V2 Z3V3 ISO Deep Groove Ball Bearing SKF NSK NTN NACHI Koyo FAG OEM

Bearing No. 6006

Size	30x55x13 mm
Bore Diameter	30 mm
Outer Diameter	55 mm
Width	13 mm
d	30 mm
D	55 mm
B	13 mm
C	13 mm
r min.	1 mm
da min.	35 mm
Da max.	50 mm
ra max.	1.0 mm
Weight	0.117 Kg
Basic dynamic load rating (C)	13,2 kN
Basic static load rating (C0)	8,3 kN
(Grease) Lubrication Speed	12000 r/min
Enclosure	Open
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	30 mm
Outside Diameter	55 mm
Width	13 mm
Fillet Radius/Chamfer	1 mm
Dynamic Load Rating	13,200 N



Mingda Bearing Products co., LTD

Static Load Rating	8,300 N
Limiting Speed - Grease	13,000 rpm
Limiting Speed - Oil	15,000 rpm
Factor fo	14.8
Radial Clearance	0.005 to 0.020 mm
da (min)	35 mm
Da (max)	50 mm
ra (max)	1 mm